

Variable Level Control Switch

Simplex Or Duplex Control Switch For Dewatering, Effluent And Sewage Applications



Zoeller Pump Company's variable level control switches can be used to monitor liquid level conditions and activate control panels or alarms in pump chambers, dose tanks, sump pump basins, holding tanks, lift stations, and other non-potable water applications. The variable level control switch is normally open when hanging vertically above the liquid level. When the water level rises and the switch is raised a few degrees above the horizontal position the switch closes, completing the circuit to the control panel or alarm. The float that encases the mechanical switch is constructed of durable PVC/polypropylene. Cord lengths of 15', 25', 35', and 50' (5, 8, 11, and 15 m) are available.

Features

- For use with control panels and alarms in non-potable water applications
- Standard variable level switches rated for 115/230 V, 5 Amps
- Standard mechanical switches rated for 115 or 230V, various amperages
- Standard switches include 18/2 Type SJOW CPE cord
- Mounting clamp and hardware included



Trusted. Tested. Tough.®

zoellerpumps.com 800-928-7867
3649 Cane Run Road, Louisville, KY 40211 USA

CL0112
0121
Supersedes
0419



Simplex or duplex control switch for dewatering, effluent and sewage applications.

Variable Level Control Switches	
Part Number	Description
10-0689	Float weight
10-0743	Mechanical float, 15' cd
10-0744	Mechanical float, 20' cd
10-1456	Float tree
10-1457	Qty 3 mechanical float 5 & clamp mount tree, 15' cd
10-1458	Qty 4 mechanical float 5 & clamp mount tree, 15' cd
10-1877	Mechanical float, 25' cd
10-1879	Mechanical float, 50' cd
10-1887	Qty 4 mechanical floats & clamp mount tree, 15' cd