

Model LM44

Floor Sucker® Utility Pump

Use the Floor Sucker® submerged or on any flat surface to pump clear water.

- 1-year warranty
- 1/4 HP, 115 V 1 Ph
- Performance up to 20' (6 m)
- Flows up to 1,800 GPH (30 GPM)
- Engineered plastic body
- Thermal overload protection
- Pumps down to 1/8"
- Fully submersible
- Automatic operation*

* Model LM44 is not to be used as a sump pump. Pump will turn on every 3 minutes for 5 seconds. If it senses water, it will continue to pump; if it does not sense water, it will turn off.



ZOELLER®
PUMP COMPANY

Trusted. Tested. Tough.®

zoellerpumps.com 800-928-7867
3649 Cane Run Road, Louisville, KY 40211 USA

FM3114
0422
Supersedes
0920


Model LM44 Floor Sucker® Utility Pump

Use the Floor Sucker® submerged or on any flat surface to pump clear water*.

TOTAL DYNAMIC HEAD/FLOW
PER MINUTE
EFFLUENT AND DEWATERING

MODEL		44	
Feet	Meters	Gal.	Liters
5	1.5	30	114
10	3.0	22	83
15	4.6	12	45
Shut-off Head:		20 ft. (6.1 m)	

014065



014065 B

Product Specifications

Model	Seal	Mode	Volts	Ph	Amps	HP	Hz	Lbs	Kg	Max Width	Max Height
LM44	Single	Auto	115	1	2.5	1/4	60	9	4	6" (15 cm)	11-3/4" (30 cm)